

# Formally Verified Autonomous Hybrid Control

**Dane A. Sabo**  
dane.sabo@pitt.edu

**Dr. Daniel G. Cole**  
dgcole@pitt.edu

University of Pittsburgh


November 30, 2025



# The United States stands on the precipice of a severe energy crisis

## Electricity consumption at U.S. data centers is expected to more than double by 2030

Total electricity consumption by U.S. data centers (terawatt-hours)




Source: Pew Research Center, Data from IEA

How much baseload power increase is this?

# The United States stands on the precipice of a severe energy crisis

## Electricity consumption at U.S. data centers is expected to more than double by 2030

Total electricity consumption by U.S. data centers (terawatt-hours)



Source: Pew Research Center, Data from IEA

How much baseload power increase is this?




30 gigawatts!

# The United States stands on the precipice of a severe energy crisis

**Electricity consumption at U.S. data centers is expected to more than double by 2030**

Total electricity consumption by U.S. data centers (terawatt-hours)



Source: Pew Research Center, Data from IEA

How much baseload power increase is this?



30 gigawatts!

# Staffing these new reactors will be an incredible challenge

How many reactor operators are required to staff this new fleet?



For one Small Modular Reactor (SMR)...

# Staffing these new reactors will be an incredible challenge

How many reactor operators are required to staff this new fleet?



For one Small Modular Reactor (SMR)...



2 Senior Reactor Operators



2 Reactor Operators

# Staffing these new reactors will be an incredible challenge

How many reactor operators are required to staff this new fleet?



For one Small Modular Reactor (SMR)...

24/7 operations require ~6 shifts:



12 SROs

12 ROs

24 licensed operators per reactor

# Staffing these new reactors will be an incredible challenge

How many reactor operators are required to staff this new fleet?



For one Small Modular Reactor (SMR)...

24/7 operations require  $\sim 6$  shifts:



12 SROs



12 ROs



24 licensed operators per reactor

**To meet demand we require 2,400 new licensed operators!**



# Staffing these new reactors will be an incredible challenge

How many reactor operators are required to staff this new fleet?



For one Small Modular Reactor (SMR)...

24/7 operations require  $\sim 6$  shifts:



12 SROs



12 ROs



24 licensed operators per reactor

**To meet demand we require 2,400 new licensed operators!**

*We currently have only 3,600 licensed operators total...*

# Nuclear reactors are operated with prescriptive handbooks and legacy control technologies



# Human reactor operators have key limitations that limit nuclear buildout

Humans cannot meet labor demand



# Human reactor operators have key limitations that limit nuclear buildout

Humans cannot meet labor demand




Procedures are not exhaustively verified



# Human reactor operators have key limitations that limit nuclear buildout

Humans cannot meet labor demand



Procedures are not exhaustively verified



Human factors cannot be trained away



The goal of this research is to create verified autonomous control systems

If this research is successful, we will be able to do the following:

# The goal of this research is to create verified autonomous control systems

If this research is successful, we will be able to do the following:

- 1 Translate written procedures into discrete control logic

# The goal of this research is to create verified autonomous control systems

If this research is successful, we will be able to do the following:

- 1 Translate written procedures into discrete control logic
- 2 Verify continuous control behavior across discrete mode transitions



# The goal of this research is to create verified autonomous control systems

If this research is successful, we will be able to do the following:

- 1 Translate written procedures into discrete control logic
- 2 Verify continuous control behavior across discrete mode transitions
- 3 **Demonstrate autonomous reactor startup with verifiable safety guarantees**

# First, we will formalize written procedures into logical statements

## APPENDIX 19-1 Plant Startup from Cold Shutdown

### I. INITIAL CONDITIONS

1. Cold Shutdown - MODE 5:
  - $K_{eff} < 0.99$
  - 0% power
  - $T_{avg} < 200^{\circ}\text{F}$
2. Reactor Coolant System: solid.
3. RCS Temperature: 150 - 160°F.

**Note:**

Temperature may be less than 150°F depending upon the decay heat load of the core.

4. RCS Pressure: 320 - 400 psig
5. Steam Generators: filled to wet layout (100% wide-range level indication).
6. Secondary Systems: shutdown, main turbine and feedwater pump turbines on their turning gears.
7. Pre-Startup Checklists: completed.

### II. INSTRUCTIONS

#### A. Heatup from COLD SHUTDOWN to HOT SHUTDOWN (MODE 5 to MODE 4)

1. Permission received from Operations Supervisor for startup.
2. Begin establishing steam generator water levels to 33 ± 5% narrow-range indication.
3. Verify or establish RCP seal injection flow.

**CAUTION:**

Do not exceed a heatup rate of 100°F/hr in the pressurizer or 100°F/hr in the RCS. Do not exceed 320°F ΔT between pressurizer and spray temperature. Use auxiliary spray for pressurizer volume and coolant mixing.

4. Energize pressurizer heaters and begin pressurizer heatup.
5. Establish a pressurizer steam bubble by:
  - a. Increasing pressurizer temperature using pressurizer heaters.
  - b. Adjust charging and letdown flow to maintain pressurizer pressure at approximately 320-400 psig while reducing pressurizer level.
  - c. As pressurizer temperature approaches 428°F (saturation temperature for 320 psig), reduce pressurizer level toward 25%.

# First, we will formalize written procedures into logical statements

## APPENDIX 19-1 Plant Startup from Cold Shutdown

### I. INITIAL CONDITIONS

1. Cold Shutdown - MODE 5:
  - $K_{eff} < 0.99$
  - 0% power
  - $T_{avg} < 200^{\circ}\text{F}$
2. Reactor Coolant System: solid.
3. RCS Temperature: 150 - 160°F.

**Note:**  
Temperature may be less than 150°F depending upon the decay heat load of the core.

4. RCS Pressure: 320 - 400 psig
5. Steam Generators: filled to wet layout (100% wide-range level indication).
6. Secondary Systems: shutdown, main turbine and feedwater pump turbines on their turning gears.
7. Pre-Startup Checklists: completed.

### II. INSTRUCTIONS

#### A. Heatup from COLD SHUTDOWN to HOT SHUTDOWN (MODE 5 to MODE 4)

1. Permission received from Operations Supervisor for startup.
2. Begin establishing steam generator water levels to 33 ± 5% narrow-range indication.
3. Verify or establish RCP seal injection flow.

**CAUTION:**  
Do not exceed a heatup rate of 100°F/hr in the pressurizer or 100°F/hr in the RCS. Do not exceed 320°F ΔT between pressurizer and spray temperature. Use auxiliary spray for pressurizer volume and coolant mixing.

4. Energize pressurizer heaters and begin pressurizer heatup.
5. Establish a pressurizer steam bubble by:
  - a. Increasing pressurizer temperature using pressurizer heaters.
  - b. Adjust charging and letdown flow to maintain pressurizer pressure at approximately 320-400 psig while reducing pressurizer level.
  - c. As pressurizer temperature approaches 428°F (saturation temperature for 320 psig), reduce pressurizer level toward 25%.

USNRC HRTD

19-12

Rev 0109

## FRET Specification

INITIAL\_CONDITIONS shall satisfy:

mode = MODE\_5

$k_{eff} < 0.99$

power = 0

$t_{avg} < 200$

...

# First, we will formalize written procedures into logical statements

## APPENDIX 19-1 Plant Startup from Cold Shutdown

### I. INITIAL CONDITIONS

#### 1. Cold Shutdown - MODE 5:

- $K_{eff} < 0.99$
- 0% power
- $T_{avg} < 200^{\circ}\text{F}$

2. Reactor Coolant System: solid.
3. RCS Temperature: 150 - 160°F.

**Note:**  
Temperature may be less than 150°F depending upon the decay heat load of the core.

4. RCS Pressure: 320 - 400 psig
5. Steam Generators: filled to wet layout (100% wide-range level indication).
6. Secondary Systems: shutdown, main turbine and feedwater pump turbines on their turning gears.
7. Pre-Startup Checklists: completed.

### II. INSTRUCTIONS

#### A. Heatup from COLD SHUTDOWN to HOT SHUTDOWN (MODE 5 to MODE 4)

1. Permission received from Operations Supervisor for startup.
2. Begin establishing steam generator water levels to 33 ± 5% narrow-range indication.
3. Verify or establish RCP seal injection flow.

**CAUTION:**  
Do not exceed a heatup rate of 100°F/hr in the pressurizer or 100°F/hr in the RCS. Do not exceed 320°F ΔT between pressurizer and spray temperature. Use auxiliary spray for pressurizer volume and coolant mixing.

4. Energize pressurizer heaters and begin pressurizer heatup.
5. Establish a pressurizer steam bubble by:
  - a. Increasing pressurizer temperature using pressurizer heaters.
  - b. Adjust charging and letdown flow to maintain pressurizer pressure at approximately 320-400 psig while reducing pressurizer level.
  - c. As pressurizer temperature approaches 428°F (saturation temperature for 320 psig), reduce pressurizer level toward 25%.

USNRC HRTD

19-12

Rev 0109

## FRET Specification

INITIAL\_CONDITIONS shall satisfy:

mode = MODE\_5

$k_{eff} < 0.99$

power = 0


$t_{avg} < 200$

...


## LTN Formula

```
□ (initial → (
    mode_5_active ∧
    k_eff_subcritical ∧
    zero_power ∧
    temp_safe ∧
    ...))
```


## Second, we will use the logical formulae to generate discrete automata



# Finally, we will build continuous controllers to move between discrete states




# Finally, we will build continuous controllers to move between discrete states



## Key Challenge

Verify continuous control behavior across discrete mode transitions

# Finally, we will build continuous controllers to move between discrete states



## Key Challenge


Verify continuous control behavior across discrete mode transitions

## Reachable Set

$$\mathcal{R}(t) = \{x(t) \mid x(0) \in X_0, \dot{x} = f(x)\}$$



# Finally, we will build continuous controllers to move between discrete states



## Key Challenge

Verify continuous control behavior across discrete mode transitions

## Reachable Set

$$\mathcal{R}(t) = \{x(t) \mid x(0) \in X_0, \dot{x} = f(x)\}$$

## Barrier Certificate

$$B(x) > 0 \wedge \nabla B \cdot f(x) \leq 0 \implies x \in \text{Safe}$$

# Verified autonomous controllers can be created by building this chain of proof of correctness

- 1 Formalize regulatory procedures into FRET specifications and translate to Linear Temporal Logic (LTL)

# Verified autonomous controllers can be created by building this chain of proof of correctness

- 1 Formalize regulatory procedures into FRET specifications and translate to Linear Temporal Logic (LTL)
- 2 Synthesize discrete automata from LTL using reactive synthesis

# Verified autonomous controllers can be created by building this chain of proof of correctness

- 1 Formalize regulatory procedures into FRET specifications and translate to Linear Temporal Logic (LTL)
- 2 Synthesize discrete automata from LTL using reactive synthesis
- 3 Design continuous controllers for each discrete mode and verify safety across mode transitions using barrier certificates and reachability analysis

# Verified autonomous controllers can be created by building this chain of proof of correctness

- 1 Formalize regulatory procedures into FRET specifications and translate to Linear Temporal Logic (LTL)
- 2 Synthesize discrete automata from LTL using reactive synthesis
- 3 Design continuous controllers for each discrete mode and verify safety across mode transitions using barrier certificates and reachability analysis

**Result: Complete hybrid autonomous system with correctness guarantees by construction**


# Success will be measured through Technology Readiness Level advancement

## Why TRLs?

Bridge gap between proof-of-concept and deployment

Measure both rigor and feasibility

**TRL 3**  
Components



**Current:** TRL 2-3

**Target:** TRL 5

# Success will be measured through Technology Readiness Level advancement

## Why TRLs?


Bridge gap between proof-of-concept and deployment

Measure both rigor and feasibility

**TRL 3**  
Components



**TRL 4**  
Integration



**Current:** TRL 2-3

**Target:** TRL 5

# Success will be measured through Technology Readiness Level advancement

## Why TRLs?


Bridge gap between proof-of-concept and deployment

Measure both rigor and feasibility


**TRL 3**  
Components



**TRL 4**  
Integration



**TRL 5**  
Hardware



**Current:** TRL 2-3

**Target:** TRL 5



# Four primary risks are identified with clear mitigation and contingency plans

## 1 Computational Tractability of Synthesis

# Four primary risks are identified with clear mitigation and contingency plans

- 1 Computational Tractability of Synthesis
- 2 Discrete-Continuous Interface Complexity

# Four primary risks are identified with clear mitigation and contingency plans

- 1 Computational Tractability of Synthesis
- 2 Discrete-Continuous Interface Complexity
- 3 Procedure Formalization Completeness

# Four primary risks are identified with clear mitigation and contingency plans

- 1 Computational Tractability of Synthesis
- 2 Discrete-Continuous Interface Complexity
- 3 Procedure Formalization Completeness
- 4 **Hardware-in-the-Loop Integration**

# Broader Impact: Multi-billion dollar O&M cost reduction

## The Economic Opportunity

Datacenter electricity demand projected to reach **1,050 TWh/year** by 2030

**If supplied by nuclear power:**

$$\begin{aligned}\text{Total annual cost} &= 1,050 \text{ TWh/yr} \times \$88.24/\text{MWh} \\ &= \mathbf{\$92.7 \text{ billion/year}}\end{aligned}$$

# Broader Impact: Multi-billion dollar O&M cost reduction

## The Economic Opportunity

Datacenter electricity demand projected to reach **1,050 TWh/year** by 2030

**If supplied by nuclear power:**

$$\begin{aligned}\text{Total annual cost} &= 1,050 \text{ TWh/yr} \times \$88.24/\text{MWh} \\ &= \mathbf{\$92.7 \text{ billion/year}}\end{aligned}$$

**O&M represents 23-30% of LCOE:**

$$\begin{aligned}\text{O\&M costs} &= \$92.7\text{B} \times 0.23\text{-}0.30 \\ &= \mathbf{\$21\text{-}28 \text{ billion/year}}\end{aligned}$$

# Broader Impact: Multi-billion dollar O&M cost reduction

## The Economic Opportunity

Datacenter electricity demand projected to reach **1,050 TWh/year** by 2030

**If supplied by nuclear power:**

$$\begin{aligned}\text{Total annual cost} &= 1,050 \text{ TWh/yr} \times \$88.24/\text{MWh} \\ &= \mathbf{\$92.7 \text{ billion/year}}\end{aligned}$$

**O&M represents 23-30% of LCOE:**

$$\begin{aligned}\text{O\&M costs} &= \$92.7\text{B} \times 0.23\text{-}0.30 \\ &= \mathbf{\$21\text{-}28 \text{ billion/year}}\end{aligned}$$

# Beyond nuclear: A generalizable framework for safety-critical autonomy

## Why Nuclear First?

- Highest regulatory requirements
- Most safety-critical domain
- Procedures already documented
- Establishes regulatory pathway

## Future Applications

- Chemical process control
- Aerospace systems
- Autonomous transportation
- Critical infrastructure

**Translate procedures** → **Synthesize logic** → **Verify behavior**  
Applicable to any hybrid system with documented operational requirements



# Formally Verified Autonomous Hybrid Control

Enabling Economic Viability  
of Next-Generation Nuclear  
Power

**Dane A. Sabo**

dane.sabo@pitt.edu

**Advisor:**

Dr. Daniel G. Cole

dgcole@pitt.edu

University of Pittsburgh  
Department of Mechanical  
Engineering and Materials Science

